

热卖推荐圆柱型锂电池型号表!!!

序号	物料编号	型号	标称容量 (mAh)	标称电压 (V)	内阻 (mΩ)	最大重量 (g)	尺寸		充电电压 (V)	最大充电电流 (C)	最大持续放电电流 (C)	最大放电电流 (A)	放电截止电压 (V)
							直径 (mm, ±0.2)	高度 (mm, ±0.3)					
1	ICR18650HP-1100	18650HP	1100	3.2	≤15mΩ	40±1	≤18.2	≤65.3	4.2	3	55	60.5	2.00
2	ICR18650PC-1300	18650PC	1300	3.7	≤12	43.5±1	≤18.1	≤65.3	4.2	1	20	26	2.75
3	ICR18650HP-1500	18650HP	1500	3.7	≤20mΩ	42±1	≤18.2	≤65.3	4.2	3	20	30	2.75
4	ICR18650HP-2000	18650HP	2000	3.7	≤18mΩ	43±1	≤18.2	≤65.3	4.2	1.0	15	30	2.75
5	ICR18650MP-2000	18650MP	2000	3.7	≤30mΩ	42±1	≤18.2	≤65.3	4.2	1	5	10	2.75
6	ICR18650MP-2200	18650MP	2200	3.7	≤30mΩ	43±1	≤18.2	≤65.3	4.2	1	5	11	2.75
7	ICR18650EC-2200	18650EC	2200	3.7	≤40mΩ	44±1	≤18.1	≤65.3	4.2	0.5	1	2.2	2.75
8	INR18650EC-2600	18650EC	2600	3.7	≤45mΩ	46±1	≤18.1	≤65.3	4.2	0.5	1	2.6	2.75
9	INR18650EC-2600	18650EC	3000	3.7	≤60mΩ	49±1	≤18.1	≤65.3	4.2	0.5	0.5	1.5	2.75

东莞市锂辉电池科技有限公司

标准型号圆柱型锂电池型号表

序号	物料编号	型号	标称容量 (mAh)	标称电压 (V)	内阻 (mΩ)	最大重量 (g)	尺寸		充电电压 (V)	最大充电电流 (C)	最大持续放电电流 (C)	最大放电电流 (A)	放电截止电压 (V)
							直径 (mm, ±0.2)	高度 (mm, ±0.3)					
1	ICR18500EC-850	18500EC	850	3.7	<80	36±1	≤18.3	≤49.9	4.2	1	2	1.7	2.75
2	ICR18500EC-1000	18500EC	1000	3.7	<80	38±1	≤18.3	≤49.9	4.2	1	2	2.0	2.75
3	ICR18500EC-1100	18500EC	1100	3.7	<80	38±1	≤18.3	≤49.9	4.2	1	2	2.2	2.75
4	ICR18500EC-1200	18500EC	1200	3.7	<80	38±1	≤18.3	≤49.9	4.2	1	2	2.4	2.75
5	ICR18500EC-1300	18500EC	1300	3.7	<80	38±1	≤18.3	≤49.9	4.2	1	2	2.6	2.75
6	ICR18500EC-1400	18500EC	1400	3.7	<60	32.5±1	≤18.3	≤49.9	4.2	1	2	2.8	2.75
7	ICR18500EC-1500	18500EC	1500	3.7	<80	33±1	≤18.3	≤49.9	4.2	1	2	3.0	2.75
8	ICR18500EC-1600	18500EC	1600	3.7	<80	39±1	≤18.3	≤49.9	4.2	1	2	3.2	2.75
9	ICR18650EC-700	18650EC	700	3.7	<60	42±1	≤18.4	≤65.0	4.2	1	2	1.4	2.75
10	ICR18650EC-800	18650EC	800	3.7	<60	42±1	≤18.4	≤65.0	4.2	1	2	1.6	2.75
11	ICR18650EC-1000	18650EC	1000	3.7	<60	42±1	≤18.4	≤65.0	4.2	1	2	2.0	2.75
12	ICR18650EC-1200	18650EC	1200	3.7	<60	42±1	≤18.4	≤65.0	4.2	1	2	2.4	2.75
13	ICR18650EC-1300	18650EC	1300	3.7	<60	42±1	≤18.4	≤65.0	4.2	1	2	2.6	2.75
14	ICR18650EC-1400	18650EC	1400	3.7	<60	42±1	≤18.4	≤65.0	4.2	1	2	2.8	2.75
15	ICR18650EC-1500	18650EC	1500	3.7	<60	42±1	≤18.4	≤65.0	4.2	1	2	3.0	2.75
16	ICR18650EC-1800	18650EC	1800	3.7	<60	42±1	≤18.4	≤65.0	4.2	1	2	3.6	2.75
17	ICR18650EC-2000A	18650EC	2000	3.6	<60	45±1	≤18.3	≤65.0	4.2	1	2	4.0	2.50
18	ICR18650EC-2000	18650EC	2000	3.7	<60	42.5±1	≤18.4	≤65.0	4.2	1	2	4.0	2.75
19	ICR18650EC-2200	18650EC	2200	3.7	<60	43.5±1	≤18.4	≤65.0	4.2	1	2	4.4	2.75
20	ICR18650EC-2250	18650EC	2250	3.6	<60	45±1	≤18.4	≤65.0	4.2	1	2	4.5	2.50
21	ICR18650EC-2400	18650EC	2400	3.7	<60	45±1	≤18.4	≤65.0	4.2	1	2	4.8	2.75
22	ICR18650EC-2500	18650EC	2500	3.6	<55	44.5±1	≤18.4	≤65.0	4.2	2	2	5.0	2.50
23	ICR18650EC-2600	18650EC	2600	3.7	<60	46.5±1	≤18.4	≤65.0	4.2	1	2	5.2	2.75
24	ICR18650EC-2800B	18650EC	2800	3.75	<60	46±1	≤18.4	≤65.0	4.2	1	2	5.6	3.00
25	ICR18650EC-2800	18650EC	2800	3.7	<60	45.5±1	≤18.4	≤65.0	4.2	1	2	5.6	2.75
26	ICR18650EC-3000	18650EC	3000	3.7	<60	46.5±1	≤18.4	≤65.0	4.2	1	2	6.0	2.75
27	IMR18650NC-1200	18650NC	1200	3.7	≤60	38±1	≤18.3	≤65.5	4.2	1	2	2.4	3.00
28	IMR18650NC-1500	18650NC	1500	3.7	≤60	39±1	≤18.3	≤65.5	4.2	1	2	3.0	3.00
29	IMR18650NC-1800	18650NC	1800	3.7	≤60	40±1	≤18.3	≤65.5	4.2	1	2	3.6	3.00
30	INR18650EC-2000	18650EC	2000	3.6	≤60	42±1	≤18.3	≤65.5	4.2	1	2	4.0	2.75
31	ICR18650EC-2200	18650EC	2200	3.7	≤50	43.5±1	≤18.1	≤65.3	4.2	0.5	2	4.4	2.75
32	INR18650EC-2600	18650EC	2600	3.7	≤60	44±1	≤18.1	≤65.3	4.2	0.5	2	5.2	2.75
33	ICR18650PC-1300A	18650PC	1300	3.6	<13	42±1	≤18.4	≤65.0	4.2	2	12	15.6	2.50
34	ICR18650PC-1300	18650PC	1300	3.7	≤12	43.5±1	≤18.1	≤65.3	4.2	1	20	26.0	2.75
35	ICR18650PC-1500	18650PC	1500	3.7	≤12	43.5±1	≤18.1	≤65.3	4.2	1	20	30.0	2.75
36	ICR18650PC-1600	18650PC	1600	3.6	<30	44±1	≤18.4	≤65.0	4.2	2	8	12.8	2.50
37	ICR18650PC-2000	18650PC	2000	3.7	≤30	41.5±1	≤18.1	≤65.3	4.2	1	5	10.0	2.75
38	ICR18650PC-2000B	18650PC	2000	3.7	≤18	42.5±1	≤18.1	≤65.3	4.2	1	15	30	2.75
39	ICR18650PC-2200	18650PC	2200	3.7	≤30	43.5±1	≤18.1	≤65.3	4.2	1	5	11.0	2.75
40	ICR18650FE-1100	18650FE	1100	3.2	≤13	41.5±1	≤18.1	≤65.3	3.6	1	45	49.5	2.00
41	IFR18650FE-1500	18650FE	1500	3.2	<60	39±1	≤18.4	≤65.0	4.2	1	2	3.0	2.00
42	ICR26650EC-2600	26650EC	2600	3.7	<50	81±2	≤26.3	≤66.4	4.2	1	1	2.6	2.75
43	ICR26650EC-3000	26650EC	3000	3.7	<50	81±2	≤26.3	≤66.4	4.2	1	1	3.0	2.75
44	ICR26650EC-3500	26650EC	3500	3.7	<50	81±2	≤26.3	≤66.4	4.2	1	1	3.5	2.75
45	ICR26650EC-4200	26650EC	4200	3.7	<50	81±2	≤26.3	≤66.4	4.2	1	1	4.2	2.75
46	ICR26650EC-5000	26650EC	5000	3.7	<50	81±2	≤26.3	≤66.4	4.2	1	1	5.0	2.75
47	IFR26650FE-2200	26650FE	2200	3.2	<40	81±2	≤26.3	≤66.4	3.6	5	10	22.0	2.00
48	IFR26650FE-2700	26650FE	2700	3.2	<40	81±2	≤26.3	≤66.4	3.6	2	3	8.1	2.00
49	IFR26650FE-3000	26650FE	3000	3.2	<40	81±2	≤26.3	≤66.4	3.6	2	3	9.0	2.00

非标准型号圆柱型锂电池型号表

序号	物料编号	型号	标称容量 (mAh)	标称电压 (V)	内阻 (mΩ)	最大重量 (g)	尺寸		充电电压 (V)	最大充电电流 (C)	最大持续放电电流 (C)	最大脉冲放电电流 (C)	放电截止电压 (V)
							直径 (mm, ±0.2)	高度 (mm, ±0.3)					
1	IFR14430FE-400	14430FE	400	3.2	<100	16±1	≤13.9	≤43	3.6	2	3	3	3.00
2	ICR14430HP-550	14430HP	550	3.7	<100	18±1	≤13.9	≤43	4.2	1	2	3	3.00
3	ICR14430EC-650	14430EC	650	3.7	<100	20±1	≤13.9	≤43	4.2	1	2	3	3.00
4	ICR14430EC-700	14430EC	700	3.7	<100	16±1	≤18.4	≤65	4.2	1	2	3	3.00
5	IFR14500FE-500	14500FE	500	3.2	<80	18±1	≤13.9	≤51	3.6	2	3	3	3.00
6	ICR14500EC-800	14500EC	800	3.7	<80	19±1	≤13.9	≤51	4.2	1	2	3	3.00
7	ICR14500HP-700	14500HP	700	3.7	<80	21±1	≤13.9	≤51	4.2	1	2	3	3.00
8	ICR14650HP-1000	14650HP	1000	3.7	<70	25±2	≤14	≤65	4.2	1	2	3	3.00
9	ICR16340PC-650	16340PC	650	3.7	<40	16.5±2	≤16.1	≤34	4.2	1	10	10	3.00
10	ICR16500PC-1200	16500PC	1200	3.7	<65	28±2	≤16.1	≤50	4.2	1	2	3	3.00
11	ICR16650PC-1600	16650PC	1600	3.7	<65	38±2	≤16.1	≤65	4.2	1	2	3	3.00
12	ICR17670EC-1550	17670EC	1550	3.7	<50	39.5±1	≤17.1	≤67	4.2	1	2	3	3.00
13	ICR18350EC-900	18350EC	900	3.7	<60	22±2	≤18.1	≤35	4.2	1	2	3	3.00
14	ICR25500EC-3000	25500EC	3000	3.7	<50	83±3	≤25.1	≤49.9	4.2	1	2	3	3.00
15	ICR25500EC-3500	25500EC	3500	3.7	<50	83±3	≤25.1	≤49.9	4.2	1	2	3	3.00
16	ICR26700BD-3400	26700BD	3400	3.8	<40	100±3	≤26.3	≤70.5	4.2	1	3	3	3.00
17	ICR26700HE-5000	26700HE	5000	3.6	<40	101±3	≤26.3	≤70.5	4.2	0.5	1.5	1.5	3.00
18	IFR26700FE-3300	26700FE	3300	3.2	<40	95±3	≤26.3	≤70.5	3.6	2	3	3	3.00
19	IFR36800FE-6500	36800FE	6500	3.2	<30	183±4	≤36.65	≤81	3.6	2	3	3	3.00

磷酸铁锂圆柱型锂电池型号表

序号	物料编号	型号	标称容量 (mAh)	标称电压 (V)	内阻 (mΩ)	最大重量 (g)	尺寸		充电电压 (V)	最大充电电流 (C)	最大持续放电电流 (C)	最大脉冲放电电流 (C)	放电截止电压 (V)
							直径 (mm, ±0.2)	高度 (mm, ±0.3)					
1	IFR14430FE-400	14430FE	400	3.2	<100	16±1	≤13.9	≤43	3.6	2	3	3	3.00
2	IFR14500FE-500	14500FE	500	3.2	<80	18±1	≤13.9	≤51	3.6	2	3	3	3.00
3	IFR26700FE-3300	26700FE	3300	3.2	<40	95±3	≤26.3	≤70.5	3.6	2	3	3	3.00
4	IFR36800FE-6500	36800FE	6500	3.2	<30	183±4	≤36.65	≤81	3.6	2	3	3	3.00
5	IFR18650FE-1500	18650FE	1500	3.2	<60	39±1	≤18.4	≤65.0	4.2	1	2	2	2.00
6	IFR26650FE-2200	26650FE	2200	3.2	<40	81±2	≤26.3	≤66.4	3.6	5	10	10	2.00
7	IFR26650FE-2700	26650FE	2700	3.2	<40	81±2	≤26.3	≤66.4	3.6	2	3	3	2.00
8	IFR26650FE-3000	26650FE	3000	3.2	<40	81±2	≤26.3	≤66.4	3.6	2	3	3	2.00